



GEO Street Light



GSL100,E0422,730

| | |
|-----------------------------------|---|
| Product ID | GSL100E0422730 |
| EPD available | Yes |
| Certificates | ENEC, Zhaga-D4i |
| MinTa in °C | -40 |
| MaxTa in °C | 40 |
| IP rating | IP66 |
| IK rating | IK09 |
| Corrosion class | C4 |
| Electrical class | Class I, Class II |
| Leakage current (mA) | < 0.450 mA |
| Voltage range (V) | 198 - 264 |
| Frequency range (Hz) | 50 - 60 |
| Total power consumption (W) | 100 |
| Power factor | 0.95 |
| PstLM | <1 |
| SVM | <0.4 |
| THD | <8 |
| Surge protection (kV) | Up to 10kV (L/N - PE) |
| Driver type | On/Off, DALI2, D4i |
| Dimming capability | No dimming, DALI2, Active night |
| Control options | Zhaga up, Zhaga down, Zhaga up/down, No Zhaga |
| Driver options | Tridonic, *Other on demand |
| Number of drivers | 1 |
| Luminous flux from luminaire (lm) | 15130 |
| Efficacy (lm/W) | 151 |
| Color temperature (K) | 3000 |
| CRI (Color Rendering Index) | 70 |
| McAdam steps | 3 |
| Optic type | Asymmetric 140°x68° |
| Optic code | E0422 |
| Energy class of light source | D |

GEO Street Light



| | |
|---|--|
| LED lifetime L90B10 Ta25 (h) | 100000 |
| LED lifetime L80B10 Ta25 (h) | 110000 |
| LED lifetime L95B10 Ta25 (h) | 50000 |
| Luminous flux decline (LLMF) 50.000h Ta25 | L95 |
| Warranty period | 5 years |
| Serviceability | LED module and driver are replaceable by installer, Toolless opening |
| Main housing material | Aluminium |
| Housing color code / name | Grey (RAL 9006) |
| Finish / Coating type | Powder coating |
| Diffuser design | Transparent |
| Product Mounting | Pole |
| Diameter (mm) | 60 |
| Cable type | CYKY |
| Length (mm) | 705 |
| Width (mm) | 292 |
| Height (mm) | 187 |
| Net weight (kg) | 11.1 |
| Full product weight (kg) | 13.5 |

