Induline 67

ILL,70,DPC,840

Product ID	ILL70DPC840
EPD available	No
MinTa in °C	-40
MaxTa in °C	50
IP rating	IP67
IK rating	IK10
Electrical class	Class I, Class II
Leakage current (mA)	< 0.300 mA
Voltage range (V)	198 - 264
Frequency range (Hz)	50 - 60
Total power consumption (W)	70
Power factor	0.95
PstLM	<1
SVM	<0.4
THD	<8
Surge protection (kV)	Up to 4kV (L/N - PE)
Driver type	On/Off
Dimming capability	No dimming
Driver options	Tridonic, *Other on demand
Number of drivers	1
Luminous flux from luminaire (lm)	10500
Efficacy (lm/W)	150
Color temperature (K)	4000
CRI (Color Rendering Index)	80
McAdam steps	3
Optic type	Symmetric 130°x109°
Optic code	DPC
Energy class of light source	D
LED lifetime L90B10 Ta25 (h)	65000
LED lifetime L80B10 Ta25 (h)	100000
Luminous flux decline (LLMF) 50.000h Ta25	L90

Induline 67





Warranty period	5 years
Serviceability	LED module and driver are replaceable by installer, Toolless opening
Main housing material	Polycarbonate
Housing color code / name	Grey (RAL 9006)
Diffuser design	Frosted
Product Mounting	wall surface, ceiling surface
Cable type	Not included
Length (mm)	1500
Width (mm)	127
Height (mm)	94
Net weight (kg)	3.6
Full product weight (kg)	4.4
Recommended installation height in m	7-8m